## FUSIA DC500

Technical Data Sheet





#### **RESIN FOR STONE SETTING AND PAVE'**

FUSIA DC500 was developed for the realization of jewellery models for direct casting. FUSIA DC500 allows the building of detailed parts with high quality resolution and smooth surfaces that do not require any further manual finishing. It is the ideal material also for stones pre-setting and micropavè.

### **HINTS FOR DESIGN**

FUSIA DC500 is a photosensitive material for DWS stereolithography 3D printers, suitable for direct casting of smooth and detailed jewellery models.

### FEATURES

- Smooth Surfaces
- Detailed Models
- Solid Design
- Easy to Burn Out
- High Accuracy
- No further manual finishing needed
- Light Yellow Colour

# TECHNICAL CHARACTERISTICS OF THE LIQUID MATERIAL

Environmental Values for Use	22°C - 27°C - max, RH 40% - 60%
Appearance / Colour	Liquid / Light Yellow
Viscosity	300 ~ 400 mPa•s at 25°C
Density	1,08 g/cm <sup>3</sup>

#### TECHNICAL CHARACTERISTICS OF THE RESIN AFTER UV CURING

Surface Hardness (Shore D)	52 ~ 54
Application / Use	Direct casting

Technical specification subject to change without notice.



#### THE FUSIA SERIES

DWS srl

The Fusia series includes all the materials suitable for direct casting for jewellery and they are in-house developed by DWS. FUSIA DC500, along with the materials of the Fusia Series, was developed exclusively for DWS jewellery range 3D printers.